

MATERIAL SAFETY DATA SHEET

Omega Products International, Inc.
1681 California Avenue
Corona, CA 92881
Emergency Phone: 951-737-7447 or 800-600-6634

January 15, 2008

MANUFACTURED FOR: Omega Products International, Inc.
1681 California Avenue
Corona, CA 92881
Phone: 800.600.6634

MANUFACTURED BY: Spectrum Manufacturing Corp.
P.O. Box 2087
Peoria, AZ 85380
Emergency Phone: 623.362.0076

SECTION I: PRODUCT IDENTIFICATION

PRODUCT NAME: SIENA GROUT STAIN ST300

SECTION II: COMPONENTS

| | <u>CAS Reg. No</u> | <u>OSHA PEL</u> | <u>ACGIH TLV</u> |
|------------------------------------|--------------------|-----------------|----------------------------------|
| Acrylic Polymer dispersed in water | | Non Hazardous | |
| Limestone | 1317-65-3 | 5 | 10 mg/rn ³ resperable |
| Titanium Dioxide | 13463-67-7 | 10 | 10 mg/rn ³ resperable |
| 2-Butoxy ethanol | 000111-76-2 | 25 PPM 25 PPM | skin |
| Ammonium Hydroxide | 1335-21-6 | 50 PPM 25 PPM | |

SECTION III: PHYSICAL PROPERTY INFORMATION

Boiling Point: 212 - 400 °F
Vapor Pressure (mm Hg): Greater than 1
Vapor Density: Heavier than air
Specific Gravity (water=1): 1.1- 1.4
Solubility in Water: Dilutable
Evaporation rate: (BU*TYL ACETATE -1): Less than one
Appearance / Odor: Thick white to colored, textured mixture, mild ammonia odor, pH 8-10

SECTION IV: FIRE AND EXPLOSION HAZRD INFORMATION

Flash Point >199 F PMCC
Explosion Limits: N/A
Extinguishing Media: Carbon Dioxide, Dry Chemical, Alcohol Foam
Unusual Fire and Explosion Hazards: Closed containers may explode due to the build-up of pressure when exposed to extreme heat.
Special Fire Fighting Procedures: Full protective equipment including self-contained breathing apparatus should be used. Water may be used to cool closed containers to prevent pressure buildup.

SECTION V: REACTIVITY DATA

STABILITY- Stable
INCOMPATIBILITY- None Known
HARRDOUS DECOMPOSITION PRODUCTS- By fire: Carbon Dioxide, Carbon Monoxide

MATERIAL SAFETY DATA SHEET

Omega Products International, Inc.
1681 California Avenue
Corona, CA 92881
Emergency Phone: 951-737-7447 or 800-600-6634

January 15, 2008

HARRDOUS POLYMERIZATION- Will Not Occur

SECTION VI: FIRE AND EXPLOSION HAZARD DATA

Routes of Exposure: INHALATION - YES EYES/SKIN – YES

ACUTE Health Hazards: Irritation of eyes, skin and upper respiratory system. In a confined area, vapors in high concentration may cause headache, nausea or dizziness.

Signs and Symptoms of Overexposure: Redness and itching or burning sensation may indicate eye or excessive skin exposure.

Emergency and First Aid Procedures:

IF INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.

SKIN: Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use.

EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

IF SWALLOWED: Get medical attention.

SECTION VII: SPILL OR LEAK PROCEDURES:

Steps to be taken in case material is released or spilled: Do not allow material to flow into sewers and open bodies of water.

Ventilate and remove with inert absorbent.

Disposal Method: Waste from Latex Finishes is not hazardous.

Incinerate in approved facility. Do not incinerate closed container.

Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

SECTION VIII: PROTECTION INFORMATION

Precautions To Be Taken During Use: Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

Ventilation: Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section II is maintained below applicable exposure limits.

Respiratory Protection: If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section II.

When sanding or abrading the dried film, wear a dust mist respirator approved by NIOSH/MSHA for dust which may be generated.

Protective Gloves: Rubber

Eye Protection: Wear safety spectacles with sideshields.

Precautions to be taken in handling and storing: Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling.

Do not take internally. Keep out of the reach of children.

Date Prepared: January 15, 2008